



Healthcare Faucet

U270310

Faucet with Fixed Spout

Dimensions	Technical	Materials	Accessibility
Spout Height: 6 ¹ / ₂ " Spout Length: 6 ¹ / ₂ "	Inlet: 3/8" Female Flow Rate: 1.32 gpm - laminar Max. Operating Temp: 106°F	Construction: Chrome plated brass body and base	ADA TAS Alberta Building Code Ontario Barrier Free BC Building Code Code de Construction Québec

Description

- High spout with laminar nozzle.
- Hygienic nozzle, can be used with a quick connect and filter cartridge.
- Maximum water temperature is preset to avoid scalding.
- Water flow limited to 1.32 gpm at 43 psi.
- Activation by long handle (L = 8 1/2")
- Interior of faucet body and spout are smooth.
- Supplied with two 3/8" Stainless flexibles.
- Body, base and spout made from chromed brass.
- Reinforced attachment to the countertop.

Technical Details

- Supply: 3/8"F
- Flow Rate: 1.32 gpm at 43 psi
- Maximum Operating Temperature: 106°F
- Height Nozzle: 6¹/₂"

001	Base Model Number (must specify)
<input type="checkbox"/>	U270310 Healthcare Faucet with Removeable Spout



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov