



# Healthcare Faucet

U270320

## Faucet with Removable Spout

Dimensions	Technical	Materials	Accessibility
Spout Height: 6 <sup>1/4</sup> " Spout Length: 6 <sup>7/8</sup> "	Inlet: 3/8" Female Flow Rate: 1.32 gpm - laminar Max. Operating Temp: 106°F	Construction: Chrome plated brass body and base	ADA TAS Alberta Building Code Ontario Barrier Free BC Building Code Code de Construction Québec

### Description

- High spout that can be swiveled.
- Removable and disposable spout that can be recycled.
- Supplied with one BIOCLIP disposable spout (U270120)
- Can be used with stainless steel (U270110), BIOFIL filter (U270030) or disposable spouts (U270120).
- Maximum water temperature is set to 106°F to avoid scalding.
- Water flow limited to 1.32 gpm at 43 psi.
- Activation by long handle (L = 8 1/2")
- Interior of faucet body and spout are smooth.
- Supplied with two 3/8" stainless flexibles.
- Reinforced attachment to the countertop.

### Technical Details

- Supply: 3/8"F
- Flow Rate: 1.32 gpm at 43 psi
- Maximum Operating Temperature: 106°F
- Height Nozzle: 6 1/4"

001	<b>Base Model Number</b> (must specify)	
<input type="checkbox"/>	U270320	Healthcare Faucet with Removeable Spout
002	<b>Options</b>	
<input type="checkbox"/>	U270110	Set of 2 Stainless Steel Spouts
<input type="checkbox"/>	U270120	15 Disposable Spouts
<input type="checkbox"/>	U270030	10 BIOFIL Filtered Spouts



**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)